

NEW FROM SOLAX

X1-BOOST G4



X1-BOOST G4

2.5kW / 3.0kW / 3.3kW / 3.6kW
4.2kW / 5.0kW / 6.0kW

Features

Superior Performance

- DC Input: 200% oversizing, 16A current, 50V startup voltage
- In-built global MPP scan for higher yield efficiency

User Friendly Monitoring

- 10s level interval of data update (Optional)
- Quick and easy configuration (WiFi)

Assured Safety & Reliability

- AC/DC built-in Type II SPD (Optional) and I-V curve diagnosis supported
- Optional external RSD (Rapid Shut Down) and integrated DC AFCI protection (Optional)
- In-built export control function

Superb Adaptability

- Home EV Charger and Heat Pump Solution adaptable
- Mass management and broad extension via Datahub
- Master/Slave parallel solution via Modbus supported

Contact Us for More Information

www.solaxpower.com
AU: +61 1300 476529
DE: +49 6142 4091664

Global: +86 571-56260008
UK: +44 2476 586998
NL: +31 (0) 852 737932

info@solaxpower.com
service@solaxpower.com



DC INPUT

Max. PV array input power [Wp]	5000	6000	6600	7200	8000	10000	12000
Max. PV input voltage [V]	600	600	600	600	600	600	600
Startup voltage [V]	50	50	50	50	50	50	50
Nominal input voltage [V]	360	360	360	360	360	360	360
MPP tracker voltage range [V]	40~560	40~560	40~560	40~560	40~560	40~560	40~560
No. of MPP trackers / String per MPP tracker	2 / 1						
Max. input current per MPPT [A]	16 / 16						
Max. short circuit current per MPPT [A]	22 / 22						

AC OUTPUT

Nominal AC output power [W]	2500	3000	3300	3680	4200	5000 ^①	6000
Nominal AC output current [A]	10.9	13	14.3	16	18.3	21.7	26.1
Max. AC output apparent power [VA]	2800	3300	3630	4048 ^④	4620	5000 ^②	6000
Max. AC output current [A]	13.3	14.3	15.7	17.6 ^⑤	20.1	21.7 ^③	27.3
Nominal AC voltage / Grid voltage range [V]	220 / 230 / 240; (90-290)						
Nominal grid frequency / Grid frequency range [Hz]	50 / 60						
Displacement power factor	0.8 leading~0.8 lagging						
THDi (Rated power) [%]	<3						

SYSTEM DATA

Max. Efficiency [%]	98	98	98	98	98	98	98
Euro. Efficiency [%]	95	95	95	95	95.5	96.5	96.5
Standby consumption [W] @Night	<3						
Ingress protection	IP66						
Operating temperature range [°C]	-25~60						
Max. operation altitude [m]	4000						
Relative humidity [%]	0~100						
Typical noise emission [dB]	25						
Storage temperature [°C]	-30~70						
Dimensions (W x H x D) [mm]	404x274x146						
Weight [kg]	11						
Cooling concept	Nature cooling					Smart fan cooling (Optional)	
Communication interfaces	Pocket WiFi / (Optional: Pocket LAN / 4G) / RS485 / DRM / USB / (Optional: CT/Meter)						

PROTECTION

Over / under voltage protection	Yes
DC isolation protection	Yes
Monitoring ground fault protection	Yes
Grid monitoring	Yes
DC injection monitoring	Yes
Back feed current monitoring	Yes
Residual current detection	Yes
Anti-islanding protection	Yes
Over temperature protection	Yes
SPD (DC/AC)	Type II (Optional)
Arc-fault circuit interrupter (AFCI)	Optional
AC auxiliary power supply (APS)	Optional
DC Switch	Optional

STANDARD

Safety	IEC / EN 62109-1 / -2
EMC	EN61000-6-1 / 2 / 3 / 4, EN61000-3-2 / 3 / 11 / 12
Certification	IEC61727, EN50549, G98/G99, AS 4777.2, VDE4105, CEI 0-21, VFR, PPDS, TOR